






SIDE OF POLE MOUNTS HIGH STRENGTH UNI-SP

Industry Standard for Over 20 Years

- Six sizes available for up to three 100-watt modules or a single 60-cell or 72-cell module
- Fits pole diameters of 2-inch to 4.5-inch
- Adapts to larger poles, Rohn 25-series towers, or flat surfaces with additional fasteners
- Fit modules with mounting hole spacing of 19-inches to 39-inches
- Manufactured using corrosion-resistant 5000 series aluminum
- In stock for immediate shipment via ground carriers
- Stainless-steel fasteners

| Module Area | ASCE 7-16 Max Wind Speed** |
|---------------|----------------------------|
| 18.33 sq. ft. | 100 MPH |
| 10.65 sq. ft. | 130 MPH |
| 6.83 sq. ft. | 150 MPH |
| 4.81 sq. ft. | 180 MPH |

** Pole size and footing affects wind rating. See our engineering memo for more information.

| ITEM # | Maximum Module Area (sq. ft.) | Rail Length (inches) | Module Hole Spacing (inches) | Mounting Pole Size (inches) | Picture |
|-------------|-------------------------------|----------------------|------------------------------|-----------------------------|---|
| UNI-SP/01XX | 18.33 | 30 | 29.2 to 39.0 | 2 to 4.5 O.D.* |  |
| UNI-SP/02 | 18.33 | 45 | 18.9 to 28.7 | 2 to 4.5 O.D.* |  |
| UNI-SP/02A | 18.33 | 55 | 18.9 to 28.7 | 2 to 4.5 O.D.* | |
| UNI-SP/02X | 18.33 | 55 | 29.2 to 39.0 | 2 to 4.5 O.D.* | |
| UNI-SP/03 | 18.33 | 70 | 18.9 to 28.7 | 2 to 4.5 O.D.* |  |
| UNI-SP/03W | 18.33 | 70 | 29.2 to 39.0 | 2 to 4.5 O.D.* | |

* Mount on larger poles, Rohn 25 towers or flat surfaces with additional fasteners